Safety Data Sheet EPOXY RESIN

Page 1

Section 1: Identification

PRODUCT INDENTIFIER:	EPOXY RESIN
CHEMICAL FAMILY:	MODIFIED BISPHENOL A - EPOXY RESIN
EMERGENCY PHONE:	CHEMTREC 800-424-9300 (US) Day or night
	Customer No. 16568
MANUFACTURER:	PACE Technologies 3601 E. 34 th St., Tucson, AZ 85718 Tucson, Arizona USA Phone: +1 520-882-6598 FAX: +1 520-882-6598

Section 2: Hazard(s) Identification

GHS CLASIFICATION:	Acute toxicity, oral (Category 3) Skin corrosion/irritation (Category 2) Sensitization, Skin (Category 1B) Serious eye damage / eye irritation (Category 2) Acute toxicity, inhalation (Category 4) Germ cell mutagenicity (Category 2) Hazardous to the aquatic environment, chronic hazard (Category 2)
PICTOGRAM(s):	
SIGNAL WORD:	Danger
HAZARD STATEMENTS:	Hazard Statement(s):H301-Toxic if swallowed.H315-Causes skin irritation.H317-May cause an allergic skin reaction.H319-Causes eye irritationH332-Harmful if inhaled.H341-Suspected of causing genetic defects.H411-Toxic to aquatic life with long lasting effects.
PRECAUTIONARY STATEMENTS:	 Precautionary Statement(s): Preventions: P201- Obtain special instructions before use. P202- Do not handle until all safety precautions have been read and understood. P261-Avoid breathing P264- Wash skin thoroughly after handling. P270- Do not eat, drink or smoke when using this product.

Telephone +1-520-882-6598 · FAX +1-520-882-6599 · pace@metallographic.com Emergency phone number (CHEMTREC 800-424-9300)

DACE [®] TECHNOLOGIES www.metallographic.com	Safety Data Sheet EPOXY RESIN	Page 2
	 P271-Use only outdoors or in a well-ventilated area. P273- Avoid release to the environment. P280- Wear protective gloves/protective clothing/eye protection/face protection. P281- Use personal protective equipment as required. Response: P301+310- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P302+P352-IF ON SKIN: wash with plenty of soap and water. P304+P340-IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313- IF exposed or concerned: Get medical advice/attention P312-Call a POISON CENTER or doctor/physician if you feel unwell. P321- Specific treatment (see on this label). P330- Rinse mouth P332+P313-IF SKIN irritation occurs: Get medical advice/attention. P337-P313-IF eye irritation persists: Get medical advice/attention. P362-Take off contaminated clothing and wash before reuse. P391- Collect spillage. Hazardous to the aquatic environment 	
	 Storage: P405- Store locked up. Disposal: P501- Dispose of contents/container to Federal, State and Local Regulations. 	

Section 3: Composition/Information on Ingredients

<u>COMPONENT(S)</u>	<u>CAS NO.</u>	<u>%</u>
Bisphenol A	80-05-7	50- 100
Butyl Glycidyl Ether	2426-08-6	10- 25

Section 4: First-Aid Measures

EYE CONTACT: Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. Rinse cautiously with water for several minutes.

SKIN CONTACT: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Specific treatment (see on this label). Wash contaminated clothing before reuse. If skin irritation or rash occurs : Wash with plenty of soap and water. Get medical advice.

Copyright 2015-2023 © · All rights reserved PACE Technologies · 3601 E. 34th St · Tucson, AZ 85713 USA Telephone +1-520-882-6598 · FAX +1-520-882-6599 · pace@metallographic.com Emergency phone number (CHEMTREC 800-424-9300)

PACE [®] TECHNOLOGIES www.metallographic.com	Safety Data Sheet EPOXY RESIN	Page 3
INHALATION:	Call a POISON CENTER or doctor if you feel unwell. Remove to fresh air and keep at rest in a position comfortable for breathing.	
INGESTION :	Obtain emergency medical attention. Rinse mouth. Do NOT induce vomiting.	

Section 5: Fire-Fighting Measures

FLAMMABILITY OF THE PRODUCT:	Flash Point 164°C (327 °F).
EXTINGUISHING MEDIA: Suitable:	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Not Suitable:	Do not use water jet.
SPECIAL EXPOSURE HAZARDS:	Do not enter fire area without proper protective equipment, including respiratory protection.
HAZARDOUS COMBUSTION PRODUCTS:	Under fire conditions, hazardous fumes will be present.

Section 6: Accidental Release Measures

PERSONAL PRECAUTIONS:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
ENVIRONMENTAL PRECAUTIONS:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
LARGE SPILLS:	Stop leak if without risk. Move containers form spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulation (see section 13). Use spark-proof tools and explosion-proof equipment.
	Copyright 2015-2023 © · All rights reserved ACE Technologies · 3601 E. 34 th St · Tucson, AZ 85713 USA +1-520-882-6598 · FAX +1-520-882-6599 · <u>pace@metallographic.com</u> Emergency phone number (CHEMTREC 800-424-9300)

DACE [®] TECHNOLOGIES www.metallographic.com	Safety Data Sheet EPOXY RESIN	Page 4
	Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.	
SMALL SPILLS:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal contain. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.	

Section 7: Handling and Storage

HANDLING:	Wash thoroughly after handling. Obtain special instructions before use. Use only outdoors or in a well-ventilated area. Avoid breathing dust, fume, gas, mist, vapours, spray. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.
STORAGE:	Keep only in the original container in a cool, well ventilated place. Keep container tightly closed. Store away from Strong bases. Strong acids. Sources of ignition. Direct sunlight.

Section 8: Exposure Controls/ Personal Protection

PERSONAL PROTECTION:	Avoid all unnecessary exposure.
RESPIRATORY:	Wear approved mask.
HANDS:	Wear protective gloves.
EYES:	Chemical goggles or safety glasses.
OTHER:	Chemical goggles or safety glasses.

Section 9: Physical and Chemical Properties

SPECIFIC GRAVITY (H2O=1): 1.13	COLOR: CLEAR to LIGHT YELLOW
Vapor pressure at 20 °C (68 °F): 3.5 hPa (3 mm Hg)	FLASH POINT: 164°C (327 °F)



Safety Data Sheet EPOXY RESIN

Page 5

SOLUBILITY IN WATER: NEGLIGIBLE		
---------------------------------	--	--

IGNITION TEMPERATURE: 215°C (419 °F)

Section 10: Stability and Reactivity

STABILITY:	This product is stable.
HAZARDOUS POLYMERIZATION:	Under normal conditions of storage and use, hazardous polymerization will not occur.
CONDITIONS TO AVOID:	No further relevant information available.
MATERIALS TO AVOID:	No further relevant information available.
HAZARDOUS DECOMPOSITON PRODUCTS:	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Decomposition products may include the following materials: carbon monoxide, aldehydes, acids.

Section 11: Toxicological Information

ACUTE TOXICITY:

Ingredient Name:	LD50	Animal	Concentration
2426-08-6 butyl glycidyl ether.	Oral	Rat	2050 mg/kg
	Dermal	Rabbit	2520 mg/kg

Primary Irritant Effect

Ingredient Name:	
Skin:	Irritant to skin and mucous membranes
Eye:	Irritating effect.
Sensitization:	Sensitization possible through skin contact.
Additional toxicological information:	The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:Toxic, Irritant

Page 6

Section 12: Ecological Information

ENVIRONMENTAL EFFECTS: Toxic for fish

Section 13: Disposal Considerations

WATSE DISPOSAL: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Section 14: Transportation Information

CFR_GROUND	Not regulated in small quantities
IATA_C	Not regulated in small quantities

Section 15: Regulatory Information

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Section 16: Other Information

16.1 NFPA 704



Top, Flammability: 1 – Slight Hazard

Left, Health Hazard: 2 – Moderate Hazard

Right, Reactivity: 0 – Minimal Hazard

Bottom, Special Notice: N/A



Disclaimer:

PACE Technologies, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. PACE TECHNOLOGIES, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, PACE TECHNOLOGIES, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

DATE REVISED: 6/01/2023 DZ